

PRODUCT DATASHEET

DOWNLIGHT LED 200 25 W 6500 K WT

LEDVANCE DOWNLIGHT LED | LED downlight luminaires



AREAS OF APPLICATION

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

PRODUCT BENEFITS

- High luminous efficacy
- Direct replacement for compact fluorescent lamp downlights
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- External driver for extended flexibility (compatible with selected DALI drivers)

PRODUCT FEATURES

- Diameter of required ceiling cut-out: 150 mm or 200 mm (depending on version)
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h (at 25 °C)



TECHNICAL DATA

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	25.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Power factor λ	>0.90


Photometrical data

Color temperature	6500 K
Luminous flux	2440 lm
Light color (designation)	Cool Daylight
Color rendering index Ra	>80
Standard deviation of color matchi [PIM]	≤ 6 sdcn

Light technical data

Beam angle	100.00 °
------------	----------

Dimensions & weight



Diameter	220.0 mm
Height	67.0 mm
Mounting diameter	200 mm

Colors & materials

Body material	Aluminum
Product color	White
Cover material	Polymethylmethacrylate (PMMA)

Temperatures & operating conditions

Ambient temperature range	-20...45 °C
----------------------------------	-------------

Lifespan

Lifespan	30000 h
Number of switching cycles	100000
Lifespan L70 at 25 °C	50000 h
Lifespan L80 at 25 °C	40000 h
Lifespan L90 at 25 °C	20000 h

Additional product data

Recommended control gear	OTi DALI 25/220...240/700 LT2 (EAN: 4052899919457)
Recommended cable clamp	Style B (EAN: 4052899077881)

Capabilities

Dimmable	No
Type of connection	Terminal, 2-pin
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP20
Protection class IK (shock resistance)	IK02
Standards	CE/CB/TÜV SÜD/EAC/ROHS

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000100	DOWNLIGHT LED 200 25 W 6500 K WT	Shipping carton box 8	470 mm x 470 mm x 250 mm	55.23 dm ³	11805.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

► www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.