

PRODUCT FAMILY DATASHEET Linear LED Mobile USB

Undercabinet luminaire for flexible mounting, with motion sensor, battery-powered, rechargeable



AREAS OF APPLICATION

- For a very large range of uses
- For indoor use only
- Shelves, furniture integration or under cabinet mounting

PRODUCT BENEFITS

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation

PRODUCT FEATURES

- Housing material: aluminum
- Integrated light and motion sensor
- Switch for Auto- or On/Off-Mode
- Battery rechargeable via USB cable



| | Electrical d | Electrical data | | | | | Light Luminaire sensor data technical data | Dimensions & weight | | | |
|---------------------------|--------------------|--------------------|--------------------|---------------------------|------------------|---------------|--|---------------------|---------|---------|-------------------|
| Product description | Nominal wattage | Nominal voltage | Mains frequency | Color temper- ature | Luminous flux | Beam angle | Type of sensor | Length | Width | Height | Product weight |
| Linear LED Mobile USB 200 | 1.00 W | 4.2 V | 0 Hz | 4000 K | 69 lm | 120 ° | Motion | 200.0 mm | 50.0 mm | 22.0 mm | 212.00 g |
| Linear LED Mobile USB 300 | 1.50 W | 4.2 V | 0 Hz | 4000 K | 98 lm | 120 ° | Motion | 300.0 mm | 50.0 mm | 22.0 mm | 289.00 g |

| | Colors & materials | | | Temperatures & operating conditions | Lifespan | Capabilities | | Certificates & standards | |
|---------------------------|--------------------|---------------|------------------|-------------------------------------|----------------------------|--------------|------------------------|--------------------------|--------------------|
| Product description | Body material | Product color | Housing color | Ambient temperature range | Number of switching cycles | Dimmable | LED module replaceable | Protection class | Type of protection |
| Linear LED Mobile USB 200 | Aluminum | Silver | Silver | -20+40 °C | 12500 | No | Not replaceable | III | IP20 |
| Linear LED Mobile USB 300 | Aluminum | Silver | Silver | -20+40 °C | 12500 | No | Not replaceable | III | IP20 |

| Product description | Standards |
|---------------------------|-------------------|
| Linear LED Mobile USB 200 | CE/EAC/REACH/RoHS |
| Linear LED Mobile USB 300 | CE/EAC/REACH/RoHS |





Linear LED Mobile USB 200

Linear LED Mobile USB 300

EQUIPMENT / ACCESSORIES

- All required accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075260443 | Shipping carton box 6 | 413 mm x 161 mm x 158 mm | 1670.00 g | 10.51 dm³ |
| 4058075260474 | Shipping carton box 6 | 413 mm x 161 mm x 158 mm | 2174.00 g | 10.51 dm³ |

Product code Packaging unit (Pieces/Unit) Dimensions (length x width x height) **Gross weight** Volume

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.