

# PRODUCT DATASHEET

## TubeKIT LED 1500 21.5 W 4000 K

TubeKIT | Mobile LED batten luminaire



### AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Shelves, furniture integration or under cabinet mounting
- Direct or indirect lighting (e.g. cove lighting)
- Kitchens, workspaces

### PRODUCT BENEFITS

- Easy to use and multifunctional LED batten luminaire
- All required accessories included (screws, dowels, brackets, hook)
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Bright, robust and durable
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Homogeneous light output

### PRODUCT FEATURES

- Durable and energy-saving LED luminaire
- Mercury-free and RoHS compliant
- Clip-In technology for stationary use and hook for mobile use
- Lifetime: up to 30,000 h
- Not dimmable
- Polycarbonate housing



- Uniform illumination
- Available with luminous flux up to 750 lm, 1,700 lm, 2,000 lm (model dependent)
- Color temperatures: 3,000 K, 4,000 K
- Color rendering index  $R_a \geq 80$

## TECHNICAL DATA

### Electrical data

Nominal wattage	21.5 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

### Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool white
Luminous flux	2100 lm
Luminous efficacy	98 lm/W

### Light technical data

Beam angle	150 °
------------	-------

## Dimensions & weight



Length	1500 mm
Width	35.0 mm
Diameter	30.0 mm
Height	36.5 mm
Product weight	382.00 g
Cable length	1800 mm

### Colors & materials

Body material	Polycarbonate (PC)
Product color	White
Housing color	White
RAL number	

#### Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Temperature range in operation	-20...+45 °C

#### Lifespan

Number of switching cycles	200000
Rated lamp life time	30000 h

#### Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall
Mercury content	0.0 mg

#### Capabilities

Dimmable	No
Type of connection	Cable with Euro plug
Holder designation	G5
LED module replaceable	Not replaceable

#### Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE
ErP For end-consumer	yes
EEL of included LED module	A++/A+/A

#### Logistical data

ErP For end-consumer	yes
----------------------	-----

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075265097	Folding carton box 1	38 mm x 71 mm x 1529 mm	568.00 g	4.13 dm <sup>3</sup>
4058075265103	Shipping carton box 8	1518 mm x 303 mm x 100 mm	5402.00 g	46.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.