

PRODUCT FAMILY DATASHEET

SURFACE CIRCULAR 250

Wall and ceiling luminaire with IP44



AREAS OF APPLICATION

- Corridors
- Stairways
- Bathrooms
- Foyers

PRODUCT BENEFITS

- High luminous efficacy
- Energy savings of up to 55 % compared to luminaires that use CFL
- Easy and quick installation
- Very homogenous light
- Clear cover protects the reflector against dust and contact
- 3 years guarantee

PRODUCT FEATURES

- Beam angle: 120°
- Type of protection: IP44
- Impact resistance: IK03
- Metal housing, PMMA cover
- Ambient temperature in operation: -20...+40 °C






TECHNICAL DATA

Product description	Electrical data			Luminaire control gear data				
	Nominal wattage	Nominal voltage	Mains frequency	Ouput current	Flicker-free	Max. no. of lum. on circuit break. B16 A	Max. no. of lum. on circuit break. C10 A	Max. no. of lum. on circuit break. C16 A
SF CIRCULAR 250 13 W 3000 K IP44 WT	13.00 W	220...240 V	50/60 Hz	78 mA	Yes	41	33	53
SF CIRCULAR 250 13 W 4000 K IP44 WT	13.00 W	220...240 V	50/60 Hz	78 mA	Yes	41	33	53

Product description	Photometrical data			Light technical data	Dimensions & weight			Colors & materials		
	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter	Height	Product weight	Body material	Product color	Cover material
SF CIRCULAR 250 13 W 3000 K IP44 WT	920 lm	Warm White	>80	120 °	250.0 mm	91.0 mm	292.00 g	Steel	White	Polymethylmethacrylate (PMMA)
SF CIRCULAR 250 13 W 4000 K IP44 WT	960 lm	Cool White	>80	120 °	250.0 mm	91.0 mm	292.00 g	Steel	White	Polymethylmethacrylate (PMMA)

Product description	Temperatures & operating conditions	Lifespan			Capabilities		Certificates & standards
	Ambient temperature range	Lifespan L70/B50 at 25 °C	Lifespan L80/B10 at 25 °C	Lifespan L90/B10 at 25 °C	Dimmable	Type of connection	Protection class
SF CIRCULAR 250 13 W 3000 K IP44 WT	-20...+40 °C	30000 h	30000 h	15000 h	No	Screw terminal, 3-Pole	I
SF CIRCULAR 250 13 W 4000 K IP44 WT	-20...+40 °C	30000 h	30000 h	15000 h	No	Screw terminal, 3-Pole	I

Product description	Type of protection
SF CIRCULAR 250 13 W 3000 K IP44 WT	IP44
SF CIRCULAR 250 13 W 4000 K IP44 WT	IP44



SF CIRCULAR 250 13 W 3000 K IP44 WT, SF CIRCULAR 250 13 W 4000 K IP44 WT

SF CIRCULAR 250 13 W 3000 K IP44 WT

SF CIRCULAR 250 13 W 4000 K IP44 WT

EQUIPMENT / ACCESSORIES

– Replacement cover optional available

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075110137	Shipping carton box 5	522 mm x 302 mm x 314 mm	2475.00 g	49.50 dm ³
4058075110151	Shipping carton box 5	522 mm x 302 mm x 314 mm	2475.00 g	49.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.