

PRODUCT DATASHEETDOWNLIGHT LED SLIM SQUARE 155 12 W 6500 K

LEDVANCE DOWNLIGHT LED SLIM SQUARE | LED downlight luminaires



AREAS OF APPLICATION

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

PRODUCT BENEFITS

- Very slim housing
- Low installation depth
- High luminous efficacy
- Energy savings up to 60 % (compared to luminaires that use CFL lamps)
- Very homogenous light
- Functional design
- Easy installation with fast connection
- Simple installation thanks to integrated driver

PRODUCT FEATURES

- Small visible bezel
- Connector box with push wire terminal for tool-free connection
- Light guide made of non-yellowing PMMA for long lifetime



TECHNICAL DATA

Electrical data

Operating mode Electronic control gear (ECG)			
Nominal wattage	12.00 W		
Nominal voltage	220240 V		
Mains frequency	50/60 Hz		
Power factor λ	0.50		


Photometrical data

Color temperature	6500 K	
Luminous flux	1020 lm	
Light color (designation)	Cool Daylight	
Color rendering index Ra	>80	
Luminous efficacy	85 lm/W	
Standard deviation of color matching	<6 sdcm	

Light technical data

Beam angle	120 °

Dimensions & weight



Length	169.0 mm
Width	169.0 mm
Height	30.0 mm
Mounting length	155.0 mm
Mounting width	155.0 mm

Colors & materials

Body material	Polycarbonate (PC)
Product color	White

Temperatures & operating conditions

Ambient temperature range	040 °C

Lifespan

Lifespan L70 at 25 °C	30000 h
Number of switching cycles	50000

Additional product data

Product remark	Available from October 2017	
Mounting location	Ceiling / Wall	

Capabilities

Dimmable	No
LED module replaceable	Not replaceable

Certificates & standards

Luminous efficacy of lamp in luminaire	85 lm/W	
Protection class	II	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Standards	CE/CB/EAC	
Photobiological safety group	RG 0	

EQUIPMENT / ACCESSORIES

- Surface mounting frames available as accessories

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075052567	DOWNLIGHT LED SLIM SQUARE 155 12 W 6500 K WT	Shipping carton box 6	290 mm x 205 mm x 195 mm	11.59 dm³	2374.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.