

# PRODUCT DATASHEET

## LED FACADE BELT 11 W 3000 K RD GY

**LEDVANCE OUTDOOR LED FACADE BELT | Luminaires with modern design and light outlet up and down**



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in round and square form
- Diffuser made of opal PMMA



TECHNICAL DATA

Electrical data

Nominal wattage	11.00 W
Nominal voltage	220...240 V
Nominal current	0.057 A
Power factor λ	>0.5
Mains frequency	50/60 Hz
Operating mode	Mains voltage


Photometrical data

Luminous efficacy	35 lm/W
Luminous flux	400 lm
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	<6 sdc <sub>m</sub>

Light technical data

Beam angle	335.00 °
------------	----------

Dimensions & weight



Length	60.0 mm
Width	240.0 mm
Height	142.0 mm
Product weight	720.00 g

Colors & materials

Housing color	Gray
Product color	Gray

<b>Body material</b>	Aluminum
<b>Cover material</b>	Polymethylmethacrylate (PMMA)

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...40 °C
----------------------------------	-------------

### Lifespan

<b>Number of switching cycles</b>	15000
<b>Lifespan L70 at 25 °C</b>	30000 h

### Additional product data

<b>Mounting location</b>	Wall
<b>Product remark</b>	Available from February 2018

### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Terminal, 3-Pole (L, N, PE)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Type of protection</b>	IP54
<b>Protection class</b>	I
<b>Protection class IK (shock resistance)</b>	IK06
<b>Standards</b>	CE
<b>Photobiological safety group</b>	RG 0

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075074972	LED FACADE BELT 11 W 3000 K RD GY	Shipping carton box 6	600 mm x 220 mm x 290 mm	38.28 dm <sup>3</sup>	5616.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.